UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/565,345	12/27/2006	Sergio A. Maiocchi	084342-000000US	2236	
	7590 12/10/200 AND TOWNSEND AN	EXAMINER			
TWO EMBARCADERO CENTER			RO, BENTSU		
EIGHTH FLOO SAN FRANCIS	SCO, CA 94111-3834	ART UNIT	PAPER NUMBER		
		2837			
			MAIL DATE	DELIVERY MODE	
			12/10/2008	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

		A	pplication No.	<i>A</i>	Applicant(s)	
Office Action Summary		1	0/565,345	N	MAIOCCHI, SERG	GIO A.
		E	xaminer	P	Art Unit	
		ВІ	ENTSU RO	2	2837	
Period fo	The MAILING DATE of this commun or Reply	ication appear	s on the cover sheet	with the cor	respondence ad	idress
WHIC - Exter after - If NC - Failu Any r	ORTENED STATUTORY PERIOD F CHEVER IS LONGER, FROM THE M Issions of time may be available under the provisions SIX (6) MONTHS from the mailing date of this common period for reply is specified above, the maximum street or reply within the set or extended period for reply eply received by the Office later than three months and patent term adjustment. See 37 CFR 1.704(b).	IAILING DATE of 37 CFR 1.136(a) nunication. atutory period will ap will, by statute, cau	E OF THIS COMMUI  In no event, however, may  ply and will expire SIX (6) No  se the application to become	NICATION. y a reply be timely MONTHS from the BEANDONED (	/ filed e mailing date of this c (35 U.S.C. § 133).	
Status						
1)[\	Responsive to communication(s) file	ad on 27 Octob	her 2008			
•			tion is non-final.			
3)	Since this application is in condition	<i>′</i> —		atters nrose	ecution as to the	e merits is
٠,١	closed in accordance with the practi		•			o monto to
		00 and 01 2x p	arto quayro, 1000 c	J.D. 11, 100	0.0.210.	
Dispositi	on of Claims					
4)🛛	Claim(s) 47-68 and 84-86 is/are per	nding in the ap	plication.			
	4a) Of the above claim(s) is/are withdrawn from consideration.					
5)🛛	Claim(s) 47-53,55-57,64-68 and 84-	<u>⋅86</u> is/are allow	ved.			
6)🛛	Claim(s) 54 and 58-63 is/are rejected	d.				
7)	Claim(s) is/are objected to.					
8)□	Claim(s) are subject to restrict	ction and/or ele	ection requirement.			
Applicati	on Papers					
9)□	The specification is objected to by th	e Examiner				
-	The drawing(s) filed on <u>12 Septemb</u> e		a) 🛛 accepted or b	o)□ objected	d to by the Exar	miner.
,	- ' '			-	-	
	Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).					
11)□	11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.					
						. 6 . 6
	ınder 35 U.S.C. § 119					
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>						
2)  Notic 3) Inform	t(s) e of References Cited (PTO-892) e of Draftsperson's Patent Drawing Review (F nation Disclosure Statement(s) (PTO/SB/08) r No(s)/Mail Date	PTO-948)	Paper N	ew Summary (P No(s)/Mail Date of Informal Pate	· ·	

Application/Control Number: 10/565,345 Page 2

Art Unit: 2837

## FIRST OFFICE ACTION ----- A NONFINAL REJECTION

1. In response to the restriction requirement (mailed 5/9/2008), applicant has elected Group I, claims 47-68 and 84-86 for prosecution, presumably without traverse. All other claims have been canceled.

The examiner has imposed another restriction based on different species. See the **Examiner's Comments** in paragraph 7 below.

- 2. The drawings filed on 9/12/2008 (total 68 sheets) are acceptable.
- The following claims recited elements that have no proper antecedent basis.
   Corrections are required.
  - Claims 62 and 63, each line 2, the recitation "the flyback inductance" lacks
    antecedent basis. Claims 62 and 63 both depend on claim 58. Claim 58 does
    not define a "flyback inductance".
  - Claim 67, line 2, the recitation "means for measuring" lacks antecedent basis.
     Claim 67 depends on claim 47. Claim 47 does not define a "means for measuring". It is noted that the "means for measuring" is defined in claims 54, 58 and 60, but not in claim 47.
- 4. To improve the readability, claims 51 and 52 should be amended as follows:
  - Claim 51, line 3, between "said diode" and "if said first switch", insert --and--.

Application/Control Number: 10/565,345 Page 3

Art Unit: 2837

• Claim 52, line 4, between "electronic switch" and "if said first switch", insert --and-

-.

5. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

6. Claims 54, 58-63 are rejected under 35 U.S.C. 102(b) as being anticipated by Nayberg USPN 4,581,692.

Claims read onto Nayberg et al teaching as follows:

The claims:	Nayberg et al teaching:
Claim 54 (previously presented): A system for driving a direct-current (DC) motor under conditions of a controlled average current,	Fig. 2 (the prior art) teaches a system for driving a load 20; in the text, Nayberg does not specify the type of load, however, any dc electric load can be used, including a dc motor; the system of Fig. 2 is to control the load current; further, there is a capacitor (no reference numeral but next to the voltage sensor 45) connected in parallel to the load 20, this capacitor smooth out the current ripple (if any), thus, the capacitor controls the average current to the load 20;
a voltage of a DC power supply having a larger or smaller value than a motor nominal voltage,	Fig. 2 shows a "fluctuating" dc voltage supply 16, see column 1, line 53, the word "fluctuating"; because the dc voltage is "fluctuating", it can be larger or smaller than the nominal voltage of the load 20;
said system comprising:	

Application/Control Number: 10/565,345

Art Unit: 2837

an inductive element for connection in series with the DC motor,

said inductive element capable of operating in a buck converter at the power level required to operate said DC motor and at the frequency of a first switch;

an arrangement including a plurality of switches, diodes and a magnetic system,

said arrangement coupled to said inductive element for connecting and disconnecting a terminal of said inductive element remote from said motor to a voltage source,

said arrangement configured as circuit selected from the group consisting of:

- a forward DC-DC converter
- a push-pull DC-DC converter

Fig. 1 shows an output inductor 36 connected in series with the load 20; again, the load 20 can be any dc load including a dc motor;

the "a first switch" reads onto the thyristor 32:

the converter 22 is a buck converter because the transformer 28 is a step-down transformer;

the inductor 36 is operating with the buck converter 22 at a power level required to operate the load 20 and at the switching frequency of the thyristor 32;

Fig. 1 shows thyristor switches 32, 34; full-wave rectifier diodes 30; and a transformer 28;

the transformer 28 is a magnetic system; thus, the thyristors, the rectifier diodes and the transformer all together constitute an arrangement;

the arrangement is connected to the inductor 36;

the thyristor 32 controls connecting and disconnecting the transformer 28 from the dc voltage supply 16;

the connecting/disconnecting of the transformer 28 also connects and disconnects the terminals of the inductor 36 from the voltage supply 16; it is noted that the inductor 36 and its terminals are not a part of the load 20, thus, the inductor is remote from the load 20;

the arrangement at least is

- a forward dc-dc converter;
- a full bridge dc-dc converter;

Application/Control Number: 10/565,345

Art Unit: 2837

• a half-bridge DC-DC converter

• a diagonal-half bridge DC-DC converter

• a full bridge DC-DC converter

a capacitor arranged for connection in parallel with said motor to limit a resulting voltage over the motor, said capacitor capable of operating in a buck converter at the power level required to operate said DC motor and at the frequency of commutation of said first switch;

"a capacitor" reads onto the capacitor (no reference numeral but next to the voltage sensor 45);

the capacitor is connected in parallel with the load 20;

the capacitor has filtering effect (or smoothing effect) which limits the ac voltage peaks, thus, limiting a resulting voltage over the motor;

the capacitor cooperates with the buck converter 22 in a same manner as that of the inductor 36 cooperates with the buck converter 22, as explained previously;

means for measuring a current through the motor; and

the current sensors 41 and 51;

means for controlling operation of said arrangement dependent upon said measured current in the motor.

the logic control circuit 37 and the conduction control circuit 35 together constitute a controlling means.

Claim 58 (previously presented): A system for driving a direct-current (DC) motor under conditions of a controlled average current, a voltage of a DC power supply having a larger or smaller value than a motor nominal voltage, said system comprising:

same as that of claim 54;

a diode;

a magnetic transformer connected in series with said diode in a circuit arrangement same as the "arrangement" of claim 54;

selected from the group consisting of a flyback DC-DC converter and a ringing

the converter 22 is a flyback dc-dc converter (a buck converter);

Art Unit: 2837

choke DC-DC converter, said transformer and said diode for connection in series with the DC motor;	
a switch coupled to said magnetic transformer and said diode for connecting and disconnecting a terminal of said magnetic transformer and said diode remote from said motor to a voltage source;	same as claim 54;
a capacitor arranged for connection in parallel with said motor to limit a resulting voltage over the motor, said capacitor capable of operating in a buck converter at the power level required to operate said DC motor and at frequency of commutation of said switch;	same as claim 54;
means for measuring a current through the motor; and	same as claim 54;
means for controlling operation of said switch dependent upon said measured current in the motor.	same as claim 54.
Claim 59 (previously presented): The system according to claim 58, wherein said switch is an electronic switch.	the thyristors 32 and 34 are electronic switches.
Claim 60 (previously presented): A system for driving a direct-current (DC) motor under conditions of a controlled average current, a voltage of a DC power supply having a larger or smaller value than a motor nominal voltage, said system comprising:	same as that of claim 54;
an electronic synchronous rectification switch;	anyone of the diodes inside the full-wave rectifier 30 is an electronic synchronous rectification switch;

Art Unit: 2837

a magnetic transformer connected in series with said synchronous rectification switch in a circuit arrangement selected from the group consisting of a flyback DC-DC converter and a ringing choke DC-DC converter, said transformer and said synchronous rectification switch for connection in series with the DC motor;  a switch coupled to said magnetic transformer and said synchronous rectification switch for connecting and disconnecting a terminal of said magnetic transformer and said synchronous rectification switch remote from said motor to a voltage source;  a capacitor arranged for connection in parallel with said motor to limit a resulting voltage over the motor;  means for measuring a current through the motor; and  means for controlling operation of said switch dependent upon said measured current in the motor.	same as that of claim 54 or claim 58.
61.	same as claim 59
62 and 63.	these claims are unclear because the "flyback inductance" is undefined; however, the "flyback inductance" maybe a misprinted of "flyback converter", if this is true, then the converter 22 is a flyback converter.

Application/Control Number: 10/565,345 Page 8

Art Unit: 2837

7. **Examiner's Comments:** 

Claims 47-53, 55-57, 64-68, 84-86 are one group of claims relate to Fig. 7C of

this instant application.

Claim 54 relates to Fig. 7D.

Claims 58-63 relate to Fig. 7E.

The examiner hereby imposes a restriction requirement to examine a single

species of Fig. 7C or claims 47-53, 55-57, 64-68 and 84-86. The other species Figs. 7D

and 7E or claims 54 and 58-63 are not allowable as explained previously and the

subject matters of these claims are quite different from that of Fig. 7C. In view of the

foregoing reasons, applicant should cancel claims 54 and 58-63.

8. Claims 47-53, 55-57, 64-68 and 84-86 are allowable. These claims are allowable

because no prior art teaches a combination of circuit elements similar to that of Fig. 7C.

It is noted that the independent claims 47, 49 and 50 are claiming similar elements as

shown in that of Fig. 7C.

9. The prior art made of record and not relied upon is considered pertinent to

applicant's disclosure.

10. Any inquiry concerning this communication should be directed to BENTSU RO at

telephone number (571)272-2072.

/BENTSU RO/

Primary Examiner, Art Unit 2837